


1. Front Axle

A: EXCEPT AWD AT MODEL



H4M0999B


- | | | |
|------------------------|---------------------|-----------------|
| (1) Spring pin | (10) Boot (DOJ) | (19) Tone wheel |
| (2) Baffle plate (DOJ) | (11) Boot (BJ) | (20) Hub bolt |
| (3) Outer race (DOJ) | (12) BJ ASSY | (21) Hub |
| (4) Snap ring | (13) Baffle plate | (22) Axle nut |
| (5) Inner race (DOJ) | (14) Oil seal (IN) | |
| (6) Ball | (15) Snap ring | |
| (7) Cage | (16) Bearing | |
| (8) Circlip | (17) Housing | |
| (9) Boot band | (18) Oil seal (OUT) | |

Tightening torque: N·m (kg·m, ft·lb)

T1: 13±3 (1.3±0.3, 9.4±2.2)

T2: 186±20 (19±2, 137±14)

B: AWD AT MODEL



B4M0773B

- (1) O-ring
- (2) Baffle plate (SFJ)
- (3) Spring pin
- (4) Outer race (SFJ)
- (5) Snap ring
- (6) Trunnion
- (7) Free ring
- (8) Circlip
- (9) Boot band

- (10) Boot band
- (11) Boot (BJ)
- (12) BJ ASSY
- (13) Baffle plate
- (14) Oil seal (IN)
- (15) Snap ring
- (16) Bearing
- (17) Housing
- (18) Oil seal (OUT)

- (19) Tone wheel
- (20) Hub bolt
- (21) Hub
- (22) Axle nut

Tightening torque: N-m (kg-m, ft-lb)

T1: 13±3 (1.3±0.3, 9.4±2.2)

T2: 186±20 (19±2, 137±14)