


12. Front Grille

A: REMOVAL AND INSTALLATION

1) Remove four upper clips from body panel. To facilitate removal, press portion shown in figure using screwdriver.



2) Pull front grille to detach it from two lower clips. (Two lower clips remain on headlight.)
3) Installation is in the reverse order of removal.


NOTE:

Attach all clips to grille. Align them with clip hole in body and push them into place.


13. Door Mirror

A: REMOVAL AND INSTALLATION


1) Remove the gusset cover.



2) Remove inner remote control switch cover.




3) Remove front door trim.



4) Remove front door trim.

- 5) Disconnect the door mirror connector.
- 6) Remove the door mirror installation screws.




- 7) Installation is in the reverse order of removal.

14. Side Protector


A: REMOVAL AND INSTALLATION

Side protector consists of three parts; front fender, front door and rear door.



1. SIDE PROTECTOR FRONT FENDER PORTION

- 1) Remove bracket which secures mud guard to front fender.



- 2) Remove mud guard. <Ref. to 5-1 [W9A2].>

NOTE:

Detach the rear part of mud guard as required for the procedure. It is not necessary to remove the entire mud guard.

- 3) Use pliers to remove a clip from inside front fender. Remove it from vehicle body but keep it with side protector.
- 4) Installation is in the reverse order of removal.